

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELiTE lithium drivetrain powered by Samsung SDI lithium technology.

ELITE

ELITE® LITHIUM OR 13.5 HP

EFI GAS

2 OR 4-WHEEL

MECHANICAL BRAKE OPTIONS

LIFTED

AND

UNLIFTED

OPTIONS





ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Automatic Park Brake
- Multifunction SOC/Speedometer Gauge
- Limited Slip Differential

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Contoured Seats
- LED Headlights, Taillights and Brake Lights
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Flat DOT Windshield
- Fold-Down Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack
- Rapid On-Board Charger
- Additional Body Colors
- Limited Slip Differential

SHUTTLE 2+2

 SHUTTLE 2+2 ELİTE
 SHUTTLE 2+2 GAS

 18" TIRES
 20" TIRES

 18" TIRES
 20" TIRES

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat				
BODY & FINISH	Injection Molded TPO				
STANDARD COLOR	Patriot Blue				
DIMENSIONS					
OVERALL LENGTH	113 in (287 cm)				
OVERALL WIDTH	47 in (119 cm)				
OVERALL HEIGHT (W/ CANOPY)	76 in (193 cm)	80 in (203 cm)	76 in (193 cm)	80 in (203 cm	
OVERALL HEIGHT (W/O CANOPY)	48 in (122 cm)	52 in (132 cm)	48 in (122 cm)	52 in (132 cm)	
WHEEL BASE	65.5 in (166 cm)				
WHEEL TRACK	37 in (94 cm) Front / 38 in (97 cm) Rear				
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	4.3 in (11 cm)	5.5 in (14 cm)	
POWER			•		
POWER SOURCE	56.7V Li-Ion Battery		4-Cycle, 24.5 cu in (401cc)		
VALVE TRAIN	N/A		Single Cylinder OHV		
HORSEPOWER (KW)	11.7 hp (8.7 kW)		13.5 hp (10.1 kW)		
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary		Starter/Generator, Solid State Regulator		
BATTERY (QTY/TYPE)	2.2 Single, 56.7V Li-Ion Composite Module		One, 12V Maintenance Free		
BATTERY CHARGER	56.7V, 350W Domestic Charger, 3M Charging Cord		N/A		
KEY OR PEDAL START	Pedal				
AIR CLEANER	N/A		Industrial Rated Dry Filter		
LUBRICATION	N/A		Pressurized Oil System		
OIL FILTER	N/A		Spin-On		
COOLING SYSTEM	N/A		Air Cooled		
FUEL CAPACITY	N/A		5.96 Gallon (22.6 L) tank		

PERFORMANCE

DRIVE TRAIN

TRANSAXLE

GEAR SELECTION

REAR AXLE RATIO

SEATING CAPACITY	4-Person				
WEIGHT W/O BATTERIES	743 lb (342 kg)	782 lb (351 kg)	872 lb (396 kg)	913 lb (414 kg)	
CURB WEIGHT	790 lb (363 kg)	829 lb (372 kg)	902 (409 kg)	963 lb (437 kg)	
VEHICLE LOAD CAPACITY	800 lb (363 kg)				
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.76 m)				
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)				

Motor Shaft Direct Drive

Dash Mount Forward-Neutral-Reverse

/ Key Switch

16.99:1

Differential w/ Helical Gears

STEERING & SUSPENSION

н						
	STEERING	Self-Compensating Rack and Pinion				
	SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers				
	SERVICE BRAKE	Dual Rear Wheel Mechanical Self-adjusting Drum				
	PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement			
	TIRES (FRONT & REAR)	Hole-N-One Tires K399, 205/65-10,	Hole-N-One Tires	K399, 205/65-10		

6 Ply

CUSHMAN.COM



6 Ply

Continuously Variable Transmission

(CVT)

Forward - Reverse

11.47: 1 (Forward) / 14.35:1 (Reverse)